SAFEBASEMENTS"

100' Floor Liner

SKU: 3-0102

PRODUCT NAME:

SafeBasements[™] Floor Liner

MANUFACTURER:

SafeBasements, Inc. 28272 Minnie St Paynesville, MN 56362 1-888-963-6892 safebasementsinc.com



BASIC USE:

SafeBasements™ Floor Liner is a high performance crawl space vapor barrier designed to prevent moisture migration from the soil into the crawl space. SafeBasements™ Floor Liner helps guard against mold, mildew, allergens, fungus, radon gas, methane gas, heat loss due to damp insulation, wood rot, and overall degradation of the crawl space.

COMPOSITION & MATERIALS:

The SafeBasements[™] Floor Liner is a white polyethylene coated drainage fabric.

SafeBasements™ Floor Liner is manufactured using woven high-density fibers yielding high strength-to-weight ratio, tensile strength and puncture resistance.

SIZE:

94" x 100'

WEIGHT:

Approximately 55 lbs per MSF

WARRANTY:

The SafeBasements™ Inc. warranties all vapor barrier material to be free from manufacturing defects, degradation, and off gassing for a period of 25 years. For more warranty information call 888-963-6892.

SAFEBASEMENTS"

100' Floor Liner



PROPERTIES	TEST METHOD	SAFEBASEMENTS 45 MIL GROUND VAPOR BARRIER	
THICKNESS (NOMINAL)	ASTM D5199	45 mil Nominal	
CLASSIFICATION	ASTM E 1745	A, B, C	
TEAR STRENGTH	ASTM D 1117-97	Warp 62.8, Weft 87.0	
TENSILE STRENGTH	ASTM D 751	290 lbf (directional average)	
PUNCTURE RESISTANCE	ASTM D 4833-07	100.5 lbf	
US PERMS	ASTM E 96	0.00 perms (average)	
FIRE RATING	ASTM E 84	Class 1 or Class A	
		Flame Spread Index (FSI)	SMOKED DEVELOPED INDEX (SDI)
		15	65

